











## AVAILABLE BLADES



























































- For cutting porcelain, single-double fired, marble and granite.
- Maximum length of cut 120 cm (47 1/4").
- Maximum depth of cut 55 mm (2 1/8") in single pass; 65 mm (2 1/2") in double pass.
- Diamond blade Ø 250 mm (10").
- Plunge cut and adjustable cutting depth.
- Heavy Duty water pump. High capacity double jet water cooling.
- Sliding bar, pivots and disc cover in aluminum.
- Easy-to-remove aluminum work benches for easy cleaning and maximum sturdiness.
- Coated metal frame.
- Re-adjustable aluminum square.
- Motor moves on 4 polypropylene pulleys.; each pulley is reinforced with 2 inside bearings.

- Pulleys are easy to re-adjust (tighten): avoid play and confer long lasting precision of cut.
- Motor held by galvanized metal frame.
- Tiling legs.
- Tilting movement (0-47°) for 45° angle cut (jolly).
- $\bullet$  Available accessories: extra side square, self-standing side bench with rollers, 4 wheels  $+\,2$ handles kit, wheel feed kit.
- Supplied with Ø 250 mm (10") diamond disc for porcelain tiles, user manual, keys kit, dressing stone.

## MODEL SPECIFICATIONS

MODEL SPECIFICATIONS											
Part No.			M	M			•				
225MS 120EU	8024648088673	1	230 V 50 Hz	Single-phase	1,5 HP / 1,1 kW	2800	250 mm 10	" 2800			
225MS 120BR	8024648089755	1	230 V 60 Hz	Single-phase	1,5 HP / 1,1 kW	3360	250 mm 10	" 3360			
225MS 120US	8024648089779	1	110 V 60 Hz	Single-phase	1,5 HP / 1,1 kW	3360	250 mm 10	" 3360			
225MS 120GB	8024648089762	1	110 V 50 Hz	Single-phase	1,5 HP / 1,1 kW	2800	250 mm 10	" 2800			

CUTTING SPECIFICATIONS AND MACHINE DIMENSIONS / WEIGHT											
	Model										
	BOLT 120	250 mm 10"	55 mm 2 1/8"	30 mm 1 3/16"	120 cm 47 1/4"	∞	85x85 cm 33 1/7"x33 1/7"	150x56x h50 cm 59"x22"x h19 5&"	50 Kg 110.2 lbs	165x65xh 55 cm 65"x251/7" xh215/8"	66 Kg 145.5 lbs







