









AVAILABLE BLADES

























Motor held by galvanized metal frame.

 $\bullet$  Tilting movement (0-47°) for 45° angle cut (jolly).







TECHNICAL CHARACTERISTICS























• Tiling legs.

stone.





• Pulleys are easy to re-adjust (tighten): avoid play and confer long lasting precision of cut.

ullet Available accessories: extra side square, self-standing side bench with rollers , 4 wheels + 2

• Supplied with Ø 250 mm (10") diamond disc for porcelain tiles, user manual, keys kit, dressing

- For cutting porcelain, single-double fired, marble and granite.
- Maximum length of cut 90 cm (35 1/2").
- $\bullet$  Maximum depth of cut 55 mm (2 1/8") in single pass; 65 mm (2 1/2") in double pass.
- Diamond blade Ø 250 mm (10").
- Plunge cut and adjustable cutting depth.
- Heavy Duty water pump. High capacity double jet water cooling.
- Sliding bar, pivots and disc cover in aluminum.
- Easy-to-remove aluminum work benches for easy cleaning and maximum sturdiness.
- Coated metal frame.
- Re-adjustable aluminum square.
- Motor moves on 4 polypropylene pulleys.; each pulley is reinforced with 2 inside bearings.

MODEL SPECIFICATIONS											
Part No.			M	<b>W</b>			•				
225MS 90EU	8024648088659	1	230 V 50 Hz	Single-phase	1,5 HP / 1,1 kW	2800	250 mm 10"	2800			
225MS 90BR	8024648089717	1	230 V 60 Hz	Single-phase	1,5 HP / 1,1 kW	3360	250 mm 10"	3360			
225MS 90US	8024648089731	1	110 V 60 Hz	Single-phase	1,5 HP / 1,1 kW	3360	250 mm 10"	3360			
225MS QOGR	8024648089724	1	110 V 50 Hz	Single-phase	15 HP / 11 kW	2800	250 mm 10"	2800			

CUTTING SPECIFICATIONS AND MACHINE DIMENSIONS / WEIGHT											
	Model										2
	BOLT 90	250 mm 10"	55 mm 2 1/8"	30 mm 1 3/16"	90 cm 35 1/7"	∞	63x63 cm 25"x25"	120x56x h50 cm 47 1/4"x22"x h19 5/8"	46 Kg 101 4 lbs	130x58xh 55 cm 51 1/8"x23"xh 21 5/8"	56 Kg 123 5 lbs

